

Product Specifications

BANNERSHOP.com.au

Double Sided - Blockout Fabric Dye Sub

PRODUCT NAME		Double Sided - Blockout Fabric Dye Sub
Category	Fabric	
Available Sizes	Custom size: Min: 210mm x 297mm (A4) Max: 5000mm x 1400mm (Without Joins)	
Product Dimensions (W x H x D)	Custom	
Base Material	250GSM Blockout Fabric Heavy Duty Fabric Matt Finish Dye Sublimation Print	
Base Finishing	Trim to Size (Hot Knife)	
Print Resolution	720DPI Photographic Print	

OPTIONAL UPGRADES	
Upgrade Material	N/A
Finishing Options	Trim to Size (Hot Knife) Sew Custom Size Pocket Sew Custom Size WHITE Pocket Re-enforced Eyelets in Corners Sew Single or Double Edge Sew Edge with Eyelets Sew Closed Pocket with 16mm/20mm/25mm Plastic Rod and Eyehooks Flag Tape with Sister Clips Sew Velcro Hook 25mm/50mm Custom Finishing
Hardware Options	N/A
Related Products	N/A

ARTWORK INFORMATION	
Artwork Dimensions - Front (W x H)	Custom
Artwork Dimensions - Back (W x H)	N/A
No. of Graphic Areas	2

USAGE INFORMATION	
Ideal Applications	Indoor Hanging Banners, Flags, Window Displays, Brightly Lit Environments
Key Benefits	High Resolution Print (Photo Quality), Custom Size and Finishing, Double Sided Solid Images with Blockout Layer, Prevents Images Casting Shadow on Reverse Side
Indoor/Outdoor Recommendation	Indoor

PACKAGING & DELIVERY INFORMATION	
Standard Turnaround Time	4 Business Days - Dispatch on the 5th day
Max Size Before Join	5000mm x 1400mm
Packaged Dimensions (W x H x D)	Based on Banner Size
Packaged Weight	Based on Banner Size
Package Type	Rolled on Cardboard Tube or Packed in Box with External Protection (may be folded prior to rolling for transportation purposes)

WARRANTY AND CARE INFORMATION	
Warranty	1 year
Life expectancy	Ink: Up to 36 months
Care instructions	Warm Gentle Machine Wash, Do not Bleach, Warm Iron. Dry Cleanable
	Minimum Artwork Resolution 150DPI
	Keep Away from Sharp Objects and Handle With Care
Fire Retardant	Fire Retardant This material has been tested & classified in accordance with Australian-New Zealand AS1530 Part 3 and has achieved very low Smoke Developed Index 0-1 out of range 0-10 and very low Spread of Flame Index 0 out of range 0-10